

NOMACORC

Select Green



synthetic

Green Line | Bio-based | 100 | 300 | 500

The world's first Net Zero Carbon Footprint closure for Super Premium Wines

Select Green uses NOMACORC's proprietary technology to provide a range of 3 different closures with their own controlled and consistent oxygen ingress. This allows a perfect wine shelf life management to better respect the winemaker intention.

PREMIUM FEATURES INCLUDE:



Recyclable



World's first closure with Net Zero Carbon Footprint



Distinct and controlled O₂ ingress



Super Premium design



TCA-free and fault free

- Unique sustainability properties

- Four distinct oxygen ingress rates, providing the winemaker control over oxygen levels allowed into the bottle so the wine develops as intended

	Select Green 100	Select Green 300	Select Green 500
Oxygen Ingress per Bottle	0.4 mg of O ₂ After 3 Months 0.7 mg of O ₂ After 6 Months 1.2 mg of O ₂ After 12 Months 1.1 mg of O ₂ per Year, After first Yr	1.6 mg of O ₂ After 3 Months 2.1 mg of O ₂ After 6 Months 2.8 mg of O ₂ After 12 Months 1.1 mg of O ₂ per Year, After first Yr	1.8 mg of O ₂ After 3 Months 2.3 mg of O ₂ After 6 Months 3.1 mg of O ₂ After 12 Months 1.7 mg of O ₂ per Year, After first Yr
Carbon Footprint**	-1g CO ₂ eq per closure	-1.3g CO ₂ eq per closure	-1.3g CO ₂ eq per closure
Premium End Treatment	Embossed	Embossed	Embossed
Customised printing	Yes	Yes	Yes
Diameters	24 mm	24 mm	24 mm
Lengths	44 mm 47 mm	44 mm 47 mm	44 mm 47 mm
Weight / Closure	5.7g 6.1g	5.7g 6.1g	5.5g 5.9g
Extraction Force	200 N - 450 N	200 N - 450 N	200 N - 450 N

Chamfered finish only

Average values based on internal testing methodologies



Patented co-extrusion process

Our patented co-extrusion process consists of two stages. First, raw materials are mixed, melted, and extruded to create a long, foamed cylinder, forming the closure's core. Then a second extrusion process applies a flexible outer skin, which is thermally bonded to the inner cylinder. The shape is stabilized in cooling water before our high-speed cutting operation cuts the closures to the proper length. Our technology is a continuous process which ensures complete bottle-to-bottle consistency and performance. The products consist of an inner foam core which allows predictable and defined oxygen ingress rates and an outer skin material that ensures smooth extractions, reinsertions and trouble-free bottling line performance.

Premium end feature

Embossed finish provides the appearance of growth lines and lenticels for a superior premium look.

The uniformity of the cell size and density in NOMACORC products provides consistent and predictable oxygen permeation.

Soft feel skin technology

The softer flexible skin also provides robust bottling performances and is easier to grip, with more appealing, softer tactile touch.

Benefits/features

- Patented co-extrusion technology creates wine closures that provide consistent, predictable oxygen permeation, eliminating off-flavors due to oxidation, reduction, or cork taint
- Uniform, small cell structure of foamed core, combined with elastic skin, provides more precise preservation performance than that of natural, technical, agglomerated, or screw-cap closures
- State-of-the-art manufacturing technology produces closures that are identical from batch to batch, resulting in trouble-free bottling with traditional corking equipment
- Patented flexible skin ensures a long-term, tight neck seal, eliminating leakage, breakage, and crumbling
- Manufactured with food-industry-approved, inert materials
- Maintains the traditional bottle-opening ceremony

Quality/performance tested for

- Uniform foamed core cell size and density
- Dimensional consistency of length, diameter, and ovality
- Mechanical performance in extraction force; compression and recovery; wine splash; and leakage
- Sensory neutrality
- Heat resistance
- Ink adhesion

International quality certifications

- HACCP (Hazard Analysis and Critical Control Point)
- GMP (Good Manufacturing Practices)
- BRC-Packaging (British Retail Consortium – Institute of Packaging)